

P.QD.029

EASYCOAT EGGSHELL ENAMEL

SAFETY DATA SHEET

Date of revision 08/08/2025
Date of last issue 06/01/2025

EASYCOAT EGGSHELL ENAMEL

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Code	FB SERIES	Product Name	EASYCOAT EGGSHELL ENAMEL
Recommended use	A paint or paint constituent product		
Company Name	Promac Paints (Pty) Ltd		
Address	PO Box 75351 Lynwood Ridge 0040		
Telephone	012 804 7305		
Facsimile	012 804 2040		
Emergency Contact	-		
Contact	- T. Patel		
Contact number	- 012 804 7305		

SECTION 2. HAZARDS IDENTIFICATION

Overall Nature Hazardous goods
Classification reference SANS10234 (1272/2008/EC) :
Classification of the substance or mixture

(H317) Sensitisation ^ Skin, Hazard Category 1
(H351) Carcinogenicity, Hazard Category 2

GHS label elements, including precautionary statements

Signal word Warning
Pictograms



Hazard and Precautionary Statements

	Hazard Statements
(H317)	May cause an allergic skin reaction.
(H351)	Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard
	Precautionary Statements
	Prevention Statements
(P201)	Obtain special instructions before use.
(P202)	Do not handle until all safety precautions have been read and understood.
(P261)	Avoid breathing dust/fume/gas/mist/vapours/spray.
(P272)	Contaminated work clothing should not be allowed out of the workplace.
(P280)	Wear protective gloves/protective clothing/eye protection/face protection.
	Response Statements
(P302+P352)	IF ON SKIN: Wash with plenty of water/...
(P308+P313)	IF exposed or concerned: Get medical advice/attention.
(P321)	Specific treatment (see ... on this label). ... Reference to supplemental first aid instruction.
(P333+P313)	If skin irritation or rash occurs: Get medical advice/attention.
(P362+P364)	Take off contaminated clothing and wash it before reuse.
	Storage Statements
(P405)	Store locked up.
	Disposal Statements
(P501)	Dispose of contents/container to ... in accordance with local/regional/ national/international regulation

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product type : Mixture **Generic name :**

P.QD.029

EASYCOAT EGG SHELL ENAMEL








CAS No. : Not applicable **EU Index No :** Not applicable **UN No :** Not applicable Not classified as dangerous for transport

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

Name	% m/m	EC Label	CAS Number	EC Index
1 WHITE SPIRIT (WS3) Xn	2.74 %	265-191-7	064742-88-7	649-405-00-X
2 SOLVENT NAP(PETRO) HEAVY AROM (ARO2)				
	2.19 %	265-198-5	064742-94-5	649-424-00-3
3 TALC MAGNESIUM SILICATE	9.08 %		014807-96-6	o
4 TITANIUM DIOXIDE	9.68 %	236-675-5	013463-67-7	o
5 2-BUTANONE OXIME	0.28 %	202-496-6	000096-29-7	616-014-00-0
6 ZINC OXIDE	0.02 %	215-222-5	001314-13-2	030-013-00-7
7 2-(2BUTOXYETHOXY)ETHANOL	0.12 %	203-961-6	000112-34-5	603-096-00-8

Lead content ≤ 90 ppm

Classification reference SANS10234 (1272/2008/EC) of constituents

ref above table	Hazard Code	Pictogram -
1 Item 1 above	H304;H372 (central nervous system);	
2 Item 2 above	H304;	
5 Item 5 above	H351;H312;H318;H317;	  
6 Item 6 above	H400;H410;	
7 Item 7 above	H319;	
ref above table	Classification	
1 Item 1 above	Asp. Tox. 1;STOT RE 1	
2 Item 2 above	Asp. Tox. 1	
5 Item 5 above	Carc. 2;Acute Tox. 4 ;Eye Dam. 1;Skin Sens. 1	
6 Item 6 above	Aquatic Acute 1;Aquatic Chronic 1	
7 Item 7 above	Eye Irrit. 2	

SECTION 4. FIRST AID MEASURES

Inhalation Move to fresh air.
Skin Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention
Eyes Rinse immediately with plenty of water. Seek medical advice if symptoms persist.
Ingestion Wash mouth with plenty of water. Do NOT induce vomiting. seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media :
 Foam. CO2. Dry powder. Fog to cool and control. Do NOT use water jets.

Specific hazards arising from the chemical :
 Containers liable to burst in a fire.
 Flammable with toxic fumes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Contain & collect. Use an inert - NOT sawdust. Keep out of drains & sewers.
 Wear protective equipment (see Section 8). Keep unprotected persons away.
 Do not allow product to reach sewage system or any water course.
 Remove ignition sources and provide sufficient ventilation

SECTION 7. HANDLING AND STORAGE

Storage :
 Store only in designated places.
 No open flames. No smoking.
 Store containers with due care in case of fire.

Handling :
 Ensure good ventilation/exhaustion at the workplace
 Do not spray on a naked flame or any incandescent material
 Eating, drinking and smoking in work areas is prohibited
 Wash hands after use

P.QD.029

EASYCOAT EGGSHELL ENAMEL

Remove contaminated clothing and protective equipment before entering eating areas

- Inhalation** In case of insufficient ventilation, use suitable respiratory protection.
- Skin** Use barrier cream and impervious gloves.
- Eyes** Use face shield & goggles or full face respirator/hood. Avoid direct contact.
- Ingestion** Observe the rules of hygiene. Wash before eating, drinking or smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

Name	CAS Number	TWA OEL (mg/m3)	TWA OEL (ppm)	STOEL (mg/m3)	STOEL (ppm)	OEL Type	Vap.Press. (mmHg)
EASYCOAT EGGSHELL ENAMEL	Not applicable						
Components :							
WHITE SPIRIT (WS3) Xn	064742-88-7	575	100	720	125	RL	
SOLVENT NAP(PETRO) HEAVY AROM (ARO2)	064742-94-5		25			SUG	
TALC	014807-96-6	1				RD	
MAGNESIUM SILICATE	013463-67-7	10/4.				T/R	
TITANIUM DIOXIDE	000096-29-7						
2-BUTANONE OXIME	001314-13-2	10/4				T/R	
ZINC OXIDE	000112-34-5					S	0.2
2-(2BUTOXYETHOXY)ETHANOL							

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

OEL Type : Mixture

Maintain air concentrations below occupational exposure standards, using engineering controls as necessary

Appropriate hand protection and protective clothing must always be used

Keep away from foodstuffs, beverages and feed

Wash hands before breaks and at the end of work

Personal protective equipment :

Skin PPE : Overall and impervious gloves (eg nitrile rubber)

Respiratory PPE : Air purifying respirator (eg cartridge type)

Eye PPE : Faceshield or solvent resistant goggles

HMS Rating (USA) 1 - 3 - 0 - I (Health-Flam-Reactivity-PPE)

SAPMA Rating 3-H-E PPE : Gloves, Respirator and Eye protection



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Value
Appearance	Water based dispersion
Odour	Typical
pH	N/A
Boiling point	>35°C
Melting point	not available
Flash point	>23°C
Explosive prop	not available
Oxidizing prop	not available
Vapour pressure	not available
Density	1.10Kg/L±0.05
Water solubility	miscible
Fat solubility	Oil : miscible
Partition coefficient	not available
Viscosity	80-85KU
Vapour density	not available
Evaporation rate	not available
Autoignition temperature	not available
L.E.L.	not available

Promac Paints (Pty) Ltd.

Reg. No.: 1992/007244/07 VAT Nr: 4320226139
 354 Derdepoort Road, Silverton, Pretoria. P.O. Box 75351, Lynnwood Ridge, 0040
 Tel: 012 804 7305 Fax: 012 804 6188 email: info@promacpaints.co.za
 www.promacpaints.co.za

**P.QD.029****EASYCOAT EGGSHELL ENAMEL**

U.E.L. not available

% non volatile not available

SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions
 No reaction with fire-fighting water

SECTION 11. TOXICOLOGICAL INFORMATION

Name	CAS Number	LD50 Oral mg/kg	LD50 Skin mg/kg	LC50 Inhal(gas) ppmV	LC50 Inhal(mist) mg/ltr
EASYCOAT EGGSHELL ENAMEL	Not applicable	t.b.e.	333333 ATEdermal	-	-
Components :					
WHITE SPIRIT (WS3) Xn	064742-88-7	>5000 mg (Rat)			
SOLVENT NAP(PETRO) HEAVY AROM (ARO2)	064742-94-5				
TALC MAGNESIUM SILICATE	014807-96-6				
TITANIUM DIOXIDE	013463-67-7	>2000			
2-BUTANONE OXIME	000096-29-7	4000 mg (Rat)			
ZINC OXIDE	001314-13-2				
2-(2BUTOXYETHOXY)ETHANOL	000112-34-5	6560 mg (Rat)	4120 mg (Rabbit)		

Inhalation Irritating.
Skin Irritating, risk of dermatitis. May be absorbed.
Eyes Irritating.
Ingestion Irritating and nauseating.

SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove
 Aquatic toxicity : No further relevant information available
 Persistence and degradability : No further relevant information available.
 Bioaccumulative potential : No further relevant information available.
 Mobility in soil : No further relevant information available.

Available ecological data of ingredients :

Name	CAS Number	Envirodata
ZINC OXIDE	001314-13-2	E4

SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

SECTION 14. TRANSPORT INFORMATION

UN Number Not applicable Not classified as dangerous for transport

SECTION 15. REGULATORY INFORMATION

Classification reference SANS10234 (1272/2008/EC) :

Classification of the substance or mixture
 (H317) Sensitisation ^ Skin, Hazard Category 1
 (H351) Carcinogenicity, Hazard Category 2

SECTION 16. OTHER INFORMATION

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.
 IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.
 HMIS Rating (USA) : 1 - 3 - 0 - I (Health-Flam-Reactivity-PPE)

Promac Paints (Pty) Ltd.

Reg. No.: 1992/007244/07 VAT Nr: 4320226139
354 Derdepoort Road, Silverton, Pretoria. P.O. Box 75351, Lynnwood Ridge, 0040
Tel: 012 804 7305 Fax: 012 804 6188 email: info@promacpaints.co.za
www.promacpaints.co.za



P.QD.029

EASYCOAT EGGSHELL ENAMEL

—

This SDS conforms with General Administrative Regulations of 6 Sept.1996 (SANS11014:2010/ISO11014:2009)
OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)
SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)
All information is given in good faith but without guarantee in respect of accuracy.
No responsibility is accepted for errors or omissions or the consequences thereof.

(Date of last issue : 06/01/2025 Date of revision : 08/08/2025)