

**Promac Paints (Pty) Ltd.**

Reg. No.: 1992/007244/07 VAT Nr: 4320226139  
 354 Derdepoort Road, Silverton, Pretoria, P.O. Box 75351, Lynnwood Ridge, 0040  
 Tel: 012 804 7305 Fax: 012 804 6188 email: info@promacpaints.co.za  
 www.promacpaints.co.za

**P.QD.029**

E-COAT ACRYLIC PVA

**SAFETY DATA SHEET**

Date of Revision 06/01/2025  
 Date of last issue 31/05/2022

**E-COAT ACRYLIC PVA****SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Code</b>	FB SERIES	<b>Product Name</b>	E-COAT ACRYLIC PVA
<b>Recommended use</b>	A paint or paint constituent product		
<b>Company Name</b>	Promac Paints (Pty) Ltd		
<b>Address</b>	PO Box 75351 Lynwood Ridge 0040		
<b>Telephone</b>	012 804 7305		
<b>Facsimile</b>	012 804 2040		
<b>Emergency Contact</b>	- T. Patel- 012 8047305		

**SECTION 2. HAZARDS IDENTIFICATION****Overall Nature** EC Classification : Not classified as hazardous**Classification reference SANS10234 (1272/2008/EC) :****Classification of the substance or mixture**

(H316) Skin corrosion/irritation, Hazard Category 3  
 (H402) Hazardous to the aquatic environment ^ AcuteHazard, Category 2

**GHS label elements, including precautionary statements**

**Signal word** Warning  
**Pictograms** None

**Hazard and Precautionary Statements**

Hazard Statements

Causes mild skin irritation  
 Toxic to aquatic life

Precautionary Statements

Prevention Statements  
 Avoid release to the environment. – if this is not the intended use.

Response Statements

If skin irritation occurs: Get medical advice/ attention.

Disposal Statements

Dispose of contents/container in accordance with local/regional/ national/international regulations in accordance with local/regional/ national/international regulation

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Product type :** Mixture **Generic name :**  
**CAS No. :** Not applicable **EU Index No :** Not applicable **UN No :** Not applicable

<b>HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS</b>					
Name	% m/m	EC Labels	CAS Number	EC Index	
TRIMETHYL-PENTADIOL- MONOISOBUTYRATE	<1.1 %		025265-77-4	n/q	
1-2 ETHANEDIOL	<0.4 %	Xn	000107-21-1	603-027-00-1	

**Classification reference SANS10234 (1272/2008/EC) :**

EC Index Classification | Hazard Code | Note |  
 603-027-00-1 Acute Tox. 4 | H302 | |

**SECTION 4. FIRST AID MEASURES**

**Promac Paints (Pty) Ltd.**

Reg. No.: 1992/007244/07 VAT Nr: 4320226139  
 354 Derdepoort Road, Silverton, Pretoria. P.O. Box 75351, Lynnwood Ridge, 0040  
 Tel: 012 804 7305 Fax: 012 804 6188 email: info@promacpaints.co.za  
 www.promacpaints.co.za

**P.QD.029****E-COAT ACRYLIC PVA**

**Inhalation** Move to fresh air.

**Skin** Always wash after being in contact with chemical substances.

**Eyes** Rinse with plenty of water. Seek medical advice if symptoms persist.

**Ingestion** Give plenty of water/milk. Induce vomiting if patient conscious. Get medical advice.

**SECTION 5. FIRE FIGHTING MEASURES**

**Suitable extinguishing media :**

**Specific hazards arising from the chemical :**

No direct explosion hazard expected.  
 Dried residues - combustible with toxic fumes.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Contain & collect. Caution - Can make floors slippery.  
 Wear protective equipment (see Section 8). Keep unprotected persons away.  
 Do not allow product to reach sewage system or any water course.  
 Remove ignition sources and provide sufficient ventilation

**SECTION 7. HANDLING AND STORAGE****Storage :**

Alkaline - corrosive. Caution with contact with non-ferrous metals.

**Handling :**

Ensure good ventilation/exhaustion at the workplace  
 Do not spray on a naked flame or any incandescent material  
 Eating, drinking and smoking in work areas is prohibited  
 Wash hands after use  
 Remove contaminated clothing and protective equipment before entering eating areas

**Inhalation** In case of insufficient ventilation, use suitable respiratory protection.

**Skin** Observe the rules of hygiene. Wash before eating, drinking or smoking.

**Eyes** Avoid direct contact. Never touch eyes with dirty hands or gloves.

**Ingestion** Observe the rules of hygiene. Wash before eating, drinking or smoking.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS**

Name	CAS Number	TWA OEL (mg/m3)	TWA OEL (ppm)	STOEL (mg/m3)	STOEL (ppm)	OEL Type	Vap.Press. (mmHg)
E-COAT ACR PVA	-	Not applicable					
Components :							
TRIMETHYL-PENTADIOL- MONOISOBUTYRATE	025265-77-4	400	100			RL	
1-2 ETHANEDIOL	000107-21-1	60		125		RL	.07

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

OEL Type : Mixture

Maintain air concentrations below occupational exposure standards, using engineering controls as necessary  
 Appropriate hand protection and protective clothing must always be used  
 Keep away from foodstuffs, beverages and feed  
 Wash hands before breaks and at the end of work

**Personal protective equipment :**

**Skin PPE** : Overall and impervious gloves (eg nitrile rubber)  
**Respiratory PPE** : Air purifying respirator (eg cartridge type)  
**Eye PPE** : Faceshield or solvent resistant goggles

**HMS Rating (USA)** 1 - 0 - 0 - I (Health-Flam-Reactivity-PPE)  
**SAPMA Rating** 3-H-E PPE : Gloves, Respirator and Eye protection

**P.QD.029****E-COAT ACRYLIC PVA****SPRAYBOOTH****Spraybooth Type** Spraybooth complying with National Standards**Skin PPE** Nitrile Gloves**Eyes PPE** Faceshield or solvent resistant goggles**Respiratory Protection** Air supplied full facepiece or head covering respirator suitable for organic vapours/particulates**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Property	Value
Appearance	Water based emulsion
Odour	Slight
pH	8.8
Boiling point	>100°C
Melting point	not available
Flash point	n/a°C
Explosive prop	not available
Oxidizing prop	not available
Vapour pressure	not available
Density	1.318-1.418Kg/L
Water solubility	miscible
Fat solubility	Oil : insoluble
Partition coefficient	not available
Viscosity	95-100KU
Vapour density	not available
Evaporation rate	not available
Autoignition temperature	not available
L.E.L.	not available
U.E.L.	not available
% non volatile	42-47%

**SECTION 10. STABILITY AND REACTIVITY**Stable under normal conditions  
No reaction with fire-fighting water**SECTION 11. TOXICOLOGICAL INFORMATION**

Name	CAS Number	LD50 Oral	LD50 Skin	LC50 Inhal(gas)	LC50 Inhal(mist)
-	-	mg/kg	mg/kg	ppmV	mg/ltr
E-COAT ACR PVA	Not applicable	38462 ATEoral	166667 ATEdermal	333333 ATEgas	-
Components :	-----	-----	-----	-----	-----
TRIMETHYL-PENTADIOL- MONOISOBUTYRATE	025265-77-4	3200 mg (Rat)	16ml/Gg		
1-2 ETHANEDIOL	000107-21-1	5840 mg (Rat)			

<b>Inhalation</b>	Possible traces of free monomers. Can be irritating.
<b>Skin</b>	Direct contact to be avoided.
<b>Eyes</b>	Can cause damage.
<b>Ingestion</b>	Irritating and nauseating.

**SECTION 12. ECOLOGICAL INFORMATION**

May have short term environmental effects. Contain, monitor & remove  
 Aquatic toxicity : No further relevant information available  
 Persistence and degradability : No further relevant information available.  
 Bioaccumulative potential : No further relevant information available.  
 Mobility in soil : No further relevant information available.

No available ecological data of ingredients :

**Promac Paints (Pty) Ltd.**

Reg. No.: 1992/007244/07 VAT Nr: 4320226139  
354 Derdepoort Road, Silverton, Pretoria. P.O. Box 75351, Lynnwood Ridge, 0040  
Tel: 012 804 7305 Fax: 012 804 6188 email: info@promacpaints.co.za  
www.promacpaints.co.za

**P.QD.029**

E-COAT ACRYLIC PVA

**SECTION 13. DISPOSAL CONSIDERATIONS**

Can be eliminated from sewage/effluent by chemical flocculation.  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**SECTION 14. TRANSPORT INFORMATION**

**UN Number** Not applicable Not classified as dangerous for transport

**SECTION 15. REGULATORY INFORMATION****Classification reference SANS10234 (1272/2008/EC) :****Classification of the substance or mixture**

(H316) Skin corrosion/irritation, Hazard Category 3  
(H402) Hazardous to the aquatic environment ^ AcuteHazard, Category 2

**SECTION 16. OTHER INFORMATION**

IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.  
HMIS Rating (USA) : 1 - 0 - 0 - I (Health-Flam-Reactivity-PPE)

**Hazard (H) phrases associated with components**

H302 : Harmful if swallowed

**Abbreviations**

Code : Abbreviation : Meaning

Xn : : harmful

==== : :

: : Associated pictogram code shown in brackets

H302 : Acute Tox. 4 : (GHS07) Acute toxicity (oral), Hazard Category 4

==== : :

: : %m/m : Percent by mass

: ATE : Acute Toxicity Estimate

: CAS : Chemical Abstracts Service

: CHIP : Chemicals (Hazard Information and Packaging for supply)

: CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

: CNS : Central Nervous System

: DIN : Standard of the German Institute for Standardisation

: DOT : Department of Transport

: EC : European Community

: EC50 : Effective Concentration (Median) for 50% of the response under test

: ECB : European Chemicals Bureau

: ECHA : European Chemicals Agency, Helsinki ([http://echa.europa.eu/home\\_en.asp](http://echa.europa.eu/home_en.asp))

: EEC : European Economic Community

: EINECS : European Inventory of Existing Chemical Substances

: ELINCS : European List of Notified Chemical Substances

: GHS : Globally Harmonized System of Classification and Labelling of Chemicals

: HMIS : Hazardous Materials Information System (USA only)

: IATA : International Air Transport Association

: IMDG : International Maritime Dangerous Goods Code

: IMO : International Maritime Organization

: INS : Guidance on Identification and Naming of Substances under REACH, ECHA, 2007

: ISO : International Standards Organisation

: L.E.L. : Lower explosive limit

: LD50/LC50 : Median (50%) lethal dose/concentration

: mg/m3 : Milligrams per cubic meter

: MSDS : Material safety data sheet

: n.a. : Not available

: NC : No Classification

: No : Number

: OEL : Occupational exposure limit

: OEL-CL : Occupational exposure limit - control limit

: OEL-RL : Occupational exposure limit - recommended limit

: OHS Act : Occupational Health and Safety Act

: P statement : Precautionary statement

: PPE : Personal protective equipment

: ppm : Parts per million

: REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals

: RTDG : Regulations on the Transport of Dangerous Goods. Generic term that covers all modal transport regulations (ADR, RID, ADN, IMDG and ITDG)

: SABS : South African Bureau of Standards

: SANS : South African National Standards

**Promac Paints (Pty) Ltd.**

Reg. No.: 1992/007244/07 VAT Nr: 4320226139  
354 Derdepoort Road, Silverton, Pretoria. P.O. Box 75351, Lynnwood Ridge, 0040  
Tel: 012 804 7305 Fax: 012 804 6188 email: info@promacpaints.co.za  
www.promacpaints.co.za



**P.QD.029**

---

**E-COAT ACRYLIC PVA**

- : SAPMA : South African Paint Manufacturers Association
  - : SARA 313 : Toxic Release Inventory Reporting SRA Section 3
  - : SDS : Safety Data Sheet
  - : STOEL : Short-term occupational exposure limit
  - : STOT-RE : Specific Target Organ Toxicity - Repeated Exposure
  
  - : STOT-SE : Specific Target Organ Toxicity - Single Exposure
  - : TDG : Transport of Dangerous Goods
  - : TSCA : Toxic Substance Control Act (USA only)
  - : TWA : Time weighted average
  - : U.E.L. : Upper explosive limit
  - : UN : United Nations
  - : WHMIS : Workplace Hazardous Materials Information Systems (Canada only)
  - ===== :
- 

This SDS conforms with General Administrative Regulations of 6 Sept.1996 (SANS11014:2010/ISO11014:2009)  
OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)  
SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)  
All information is given in good faith but without guarantee in respect of accuracy.  
No responsibility is accepted for errors or omissions or the consequences thereof.

(Date of last issue : 31/05/2022 Date of revision : 06/01/2025)