

P.QD.029

HI HEAT

# SAFETY DATA SHEET

Date of revision 25/11/2025

Date of last issue 25/11/2025

## HI HEAT

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

|                          |                                       |                     |         |
|--------------------------|---------------------------------------|---------------------|---------|
| <b>Product Code</b>      | CD SERIES                             | <b>Product Name</b> | HI HEAT |
| <b>Recommended use</b>   | A paint or paint constituent product  |                     |         |
| <b>Company Name</b>      | Promac Paints (Pty) Ltd               |                     |         |
| <b>Address</b>           | PO Box 75351<br>Lynwood Ridge<br>0040 |                     |         |
| <b>Telephone</b>         | 012 804 7305                          |                     |         |
| <b>Facsimile</b>         | 012 804 2040                          |                     |         |
| <b>Emergency Contact</b> | -                                     |                     |         |
| <b>Contact</b>           | - T. Patel                            |                     |         |
| <b>Contact number</b>    | - 012 804 7305                        |                     |         |

### SECTION 2. HAZARDS IDENTIFICATION

**Overall Nature** Hazardous goods (Highly flammable liquid (flash-point below 23°C))

**Classification reference SANS10234 (1272/2008/EC) :**

**Classification of the substance or mixture**

- (H224) Flammable liquids, Hazard Category 1
- (H302) Acute toxicity (oral), Hazard Category 4
- (H313) Acute toxicity (dermal), Hazard Category 5
- (H332) Acute toxicity (inhalation), Hazard Category 4
- (H315) Skin corrosion/irritation, Hazard Category 2
- (H318) Serious eye damage/eye irritation, Hazard Category 1
- (H317) Sensitisation ^ Skin, Hazard Category 1
- (H341) Germ cell mutagenicity, Hazard Category 2
- (H350) Carcinogenicity, Hazard Category 1A, 1B
- (H335) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Respiratory tract irritation
- (H402) Hazardous to the aquatic environment ^ AcuteHazard, Category 3
- (H412) Hazardous to the aquatic environment ^ Chronic Hazard, Category 3

**GHS label elements, including precautionary statements**

**Signal word** Danger

**Pictograms**



#### Hazard and Precautionary Statements

**Hazard Statements**

- (H224) Extremely flammable liquid and vapour.
- (H302) Harmful if swallowed.
- (H313) May be harmful in contact with skin
- (H332) Harmful if inhaled.
- (H315) Causes skin irritation.
- (H318) Causes serious eye damage.
- (H317) May cause an allergic skin reaction.
- (H341) Suspected of causing genetic defects
- (H350) May cause cancer
- (H335) May cause respiratory irritation.
- (H402) Harmful to aquatic life

(H412) Harmful to aquatic life with long lasting effects.

**Precautionary Statements**

**P.QD.029**

**HI HEAT**

|                  |   |
|------------------|---|
|                  | <b>Prevention Statements</b>  |
| (P201)           | Obtain special instructions before use.   |
| (P202)           | Do not handle until all safety precautions have been read and understood.   |
| (P210)           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                    |
| (P233)           | Keep container tightly closed.  |
| (P240)           | Ground and bond container and receiving equipment. – if the explosive is electrostatically sensitive.                             |
| (P241)           | Use explosion-proof [electrical/ventilating/lighting/...] equipment.  |
| (P242)           | Use non-sparking tools.   |
| (P243)           | Take action to prevent static discharges.   |
| (P261)           | Avoid breathing dust/fume/gas/mist/vapours/spray.   |
| (P264)           | Wash ... thoroughly after handling.   |
| (P270)           | ?C3 Do not eat, drink or smoke when using this product. ?   |
| (P271)           | Use only outdoors or in a well-ventilated area.   |
| (P272)           | Contaminated work clothing should not be allowed out of the workplace.  |
| (P273)           | Avoid release to the environment. – if this is not the intended use.  |
| (P280)           | Wear protective gloves/protective clothing/eye protection/face protection.  |
|                  | <b>Response Statements</b>  |
| (P301+P312)      | IF SWALLOWED: Call a POISON CENTRE/doctor/... if you feel unwell.   |
| (P302+P352)      | IF ON SKIN: Wash with plenty of water/...   |
| (P303+P361+P353) | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].                          |
| (P304+P340)      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.  |
| (P305+P351+P338) | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  |
| (P308+P313)      | IF exposed or concerned: Get medical advice/attention.  |
| (P310)           | Immediately call a POISON CENTER/doctor/...   |
| (P321)           | Specific treatment (see ... on this label). ... Reference to supplemental first aid instruction.                                  |
| (P330)           | Rinse mouth.  |
| (P332+P313)      | If skin irritation occurs: Get medical advice/attention.  |
| (P333+P313)      | If skin irritation or rash occurs: Get medical advice/attention.  |
| (P362+P364)      | Take off contaminated clothing and wash it before reuse.  |
| (P370+P378)      | In case of fire: Use... to extinguish.  |
|                  | <b>Storage Statements</b>   |
| (P403+P233)      | Store in a well-ventilated place. Keep container tightly closed. – if product is volatile so as to generate hazardous atmosphere. |
| (P403+P235)      | Store in a well-ventilated place. Keep cool.  |
| (P405)           | Store locked up.  |
|                  | <b>Disposal Statements</b>  |
| (P501)           | Dispose of contents/container to ... in accordance with local/regional/ national/international regulation                         |
| (302+P312)       | not found   |

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Product type :** Mixture      **Generic name :** PAINT OR PAINT RELATED MATERIAL, FLAMMABLE  
**CAS No. :** Not applicable      **EU Index No :** Not applicable      **UN No :** 1263

**HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS**

| Name  | % m/m    | EC Label  | CAS Number  | EC Index     |
|---|----------|-----------|-------------|--------------|
| 1 PROPAN-2-OL   | 1.12     | 200-746-9 | 000071-23-8 | 603-003-00-0 |
| 2 XYLENE  | 1.98     | 215-535-7 | 001330-20-7 | 601-022-00-9 |
| 3 N-BUTANOL   | 2.48     | 200-751-6 | 000071-36-3 | 603-004-00-6 |
| 4 BUTANONE  | 20.37    | 201-159-0 | 000078-93-3 | 606-002-00-3 |
| 5 ETHYL ALCOHOL   | 25.17    | 200-578-6 | 000064-17-5 | 603-002-00-5 |
| 6 N-BUTANOL   | 28.21    | 200-751-6 | 000071-36-3 | 603-004-00-6 |
| 7 Items classified as hazardous but below reporting limit | 1.80     |           |             |              |
| 8 Items not classified as hazardous                       | 9.80     |           |             |              |
| Lead content  | ≤ 90 ppm |           |             |              |

**Classification reference SANS10234 (1272/2008/EC) of constituents**

| ref above table | Hazard Code   | Pictogram | Cutoff                 |
|-----------------|---|-----------|------------------------|
| 1 Above Item 1  | H225^H336^H318^   |           | GHS02^GHS05^!GHS07^Dgr |
| 2 Above Item 2  | H226^H332^H312^H315^  |           | GHS02^!GHS07^Wng       |
| 3 Above Item 3  | H226^H302^H335^H336^H315^H318^  |           | GHS02^GHS05^!GHS07^Dgr |
| 4 Above Item 5  | H225^H336^H319^EUH066   |           | GHS02^!GHS07^Dgr       |
| 5 Above Item 6  | H225^   |           | GHS02^Dgr              |
| 6 Above Item 7  | H226^H302^H335^H336^H315^H318^  |           | GHS02^GHS05^!GHS07^Dgr |
| ref above table | Classification  |           |                        |
| 1 Above Item 1  | Flam. Liq. 2^STOT SE 3^Eye Dam. 1                                       |           |                        |
| 2 Above Item 2  | Flam. Liq. 3^Acute Tox. 4 ^Acute Tox. 4 ^Skin Irrit. 2                  |           |                        |
| 3 Above Item 3  | Flam. Liq. 3^Acute Tox. 4 ^STOT SE 3^STOT SE 3^Skin Irrit. 2^Eye Dam. 1 |           |                        |

**Promac Paints (Pty) Ltd.**

Reg. No.: 1992/007244/07 VAT Nr: 4320226139  
354 Derdepoort Road, Silverton, Pretoria. P.O. Box 75351, Lynnwood Ridge, 0040  
Tel: 012 804 7305 Fax: 012 804 6188 email: info@promacpaints.co.za  
www.promacpaints.co.za

**P.QD.029****HI HEAT**

- |   |              |   |
|---|--------------|---|
| 4 | Above Item 5 | Flam. Liq. 2 <sup>^</sup> STOT SE 3 <sup>^</sup> Eye Irrit. 2   |
| 5 | Above Item 6 | Flam. Liq. 2  |
| 6 | Above Item 7 | Flam. Liq. 3 <sup>^</sup> Acute Tox. 4 <sup>^</sup> STOT SE 3 <sup>^</sup> STOT SE 3 <sup>^</sup> Skin Irrit. 2 <sup>^</sup> Eye Dam. 1 |

**SECTION 4. FIRST AID MEASURES**

- Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.
- Move victim to fresh air.
- Call 911 or emergency medical service.
- Give artificial respiration if victim is not breathing.
- Administer oxygen if breathing is difficult.
- Remove and isolate contaminated clothing and shoes.
- In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes.
- Wash skin with soap and water.
- In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- Keep victim calm and warm.

**SECTION 5. FIRE FIGHTING MEASURES**

CAUTION: All these products have a very low flash point: Use of water spray when fighting fire may be inefficient.

CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective.

**Small Fire**

- Dry chemical, CO2, water spray or regular foam.

**Large Fire**

- Water spray, fog or regular foam.
- Do not use straight streams.
- Move containers from fire area if you can do it without risk.

**Fire involving Tanks or Car/Trailer Loads**

- Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.
- Cool containers with flooding quantities of water until well after fire is out.
- Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.
- ALWAYS stay away from tanks engulfed in fire.
- For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

**SECTION 6. ACCIDENTAL RELEASE MEASURES****SPILL OR LEAK**

- ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
- All equipment used when handling the product must be grounded.
- Do not touch or walk through spilled material.
- Stop leak if you can do it without risk.
- Prevent entry into waterways, sewers, basements or confined areas.
- A vapor-suppressing foam may be used to reduce vapors.
- Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- Use clean, non-sparking tools to collect absorbed material.

**Large Spill**

- Dike far ahead of liquid spill for later disposal.
- Water spray may reduce vapor, but may not prevent ignition in closed spaces.

**SECTION 7. HANDLING AND STORAGE****Storage**

Store separately from : explosives, toxic gases, oxidising substances, organic peroxides, poisonous (toxic) substances, infectious

substances (biohazards),

No open flames. No smoking. No sparks.

Keep containers cool. Avoid free fall of liquid - use earthing.

Subject to local bylaws

**P.QD.029**

**HI HEAT**

Store in a well-ventilated place. Keep container tightly closed. – if product is volatile so as to generate hazardous atmosphere.  
 Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container to ... in accordance with local/regional/ national/international regulation

**Handling**

Ensure good ventilation/exhaustion at the workplace  
 Do not spray on a naked flame or any incandescent material  
 Eating, drinking and smoking in work areas is prohibited  
 Wash hands after use  
 Remove contaminated clothing and protective equipment before entering eating areas

**Inhalation** Ensure adequate ventilation or use respiratory protection. Ventilate curing areas/ovens properly.  
**Skin** AVOID CONTACT. Use impervious gloves, apron and boots.  
**Eyes** Avoid any form of direct contact. Do not touch eyes with dirty hands or gloves.  
**Ingestion** Observe the rules of hygiene. Wash before eating, drinking or smoking.

**SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**

**HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS**

| Name          | CAS Number     | TWA OEL | TWA OEL | STOEL | STOEL | OEL   | Vap.Press. |
|---------------|----------------|---------|---------|-------|-------|-------|------------|
| HI HEAT       | Not applicable |         |         |       |       |       |            |
| Components :  | -----          | -----   | -----   | ----- | ----- | ----- |            |
| PROPAN-2-OL   | 000071-23-8    | 980     | 400     | 1225  | 500   | RL -  | 44         |
| XYLENE        | 001330-20-7    | 435     | 100     | 650.  | 150.  | RL+ S | 6.7        |
| N-BUTANOL     | 000071-36-3    | 150     | 50      | 150   | 50    | RL S  | 1.3        |
| BUTANONE      | 000078-93-3    | 590.    | 200.    | 885   | 300   | RL+   | 105        |
| ETHYL ALCOHOL | 000064-17-5    | 1900    | 1000.   |       |       | RL    | 43         |

*(CL/RL = Controlled/Recommended level 'S' = Skin annotation)*

Maintain air concentrations below occupational exposure standards, using engineering controls as necessary  
 Appropriate hand protection and protective clothing must always be used  
 Keep away from foodstuffs, beverages and feed  
 Wash hands before breaks and at the end of work

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Keep container tightly closed.  
 Ground and bond container and receiving equipment. – if the explosive is electrostatically sensitive.  
 Use explosion-proof [electrical/ventilating/lighting/...] equipment.  
 Use non-sparking tools.

Take action to prevent static discharges.  
 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 Wash ... thoroughly after handling.  
 ?C3 Do not eat, drink or smoke when using this product. ?  
 Use only outdoors or in a well-ventilated area.  
 Contaminated work clothing should not be allowed out of the workplace.  
 Avoid release to the environment. – if this is not the intended use.

**P.QD.029**

**HI HEAT**

Wear protective gloves/protective clothing/eye protection/face protection.

HMS Rating (USA) 2 - 4 - 0 - I (Health-Flam-Reactivity-PPE)  
SAPMA Rating 2-H-E PPE : Gloves, Respirator and Eye protection

**Personal protective equipment :**

**Skin PPE :** Overall and impervious gloves (eg nitrile rubber)  
**Respiratory PPE :** Air purifying respirator (eg cartridge type)  
**Eye PPE :** Faceshield or solvent resistant goggles



**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

| Property                 | Value          |
|--------------------------|----------------|
| Appearance               | Viscous liquid |
| Odour                    | Pungent        |
| pH                       | <6             |
| Boiling point            | <35°C          |
| Melting point            | not available  |
| Flash point              | <23°C          |
| Explosive prop           | not available  |
| Oxidizing prop           | not available  |
| Vapour pressure          | not available  |
| Density                  | 0.886Kg/L      |
| Water solubility         | --             |
| Fat solubility           | --             |
| Partition coefficient    | not available  |
| Viscosity                | not available  |
| Vapour density           | not available  |
| Evaporation rate         | not available  |
| Autoignition temperature | not available  |
| L.E.L.                   | not available  |
| U.E.L.                   | not available  |
| % non volatile           | not available  |

**SECTION 10. STABILITY AND REACTIVITY**

Stable under normal conditions  
Prone to ignite by static  
No reaction with fire-fighting water  
Keep away from : explosives, toxic gases, oxidising substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),

**POTENTIAL HAZARDS**

**FIRE OR EXPLOSION**

- HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.
- Vapors may form explosive mixtures with air.
- Vapors may travel to source of ignition and flash back.
- Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).
- Vapor explosion hazard indoors, outdoors or in sewers.

**Promac Paints (Pty) Ltd.**

Reg. No.: 1992/007244/07 VAT Nr: 4320226139  
 354 Derdepoort Road, Silverton, Pretoria. P.O. Box 75351, Lynnwood Ridge, 0040  
 Tel: 012 804 7305 Fax: 012 804 6188 email: info@promacpaints.co.za  
 www.promacpaints.co.za

**P.QD.029****HI HEAT**

- Those substances designated with a (P) may polymerize explosively when heated or involved in a fire.
- Runoff to sewer may create fire or explosion hazard.
- Containers may explode when heated.
- Many liquids are lighter than water.
- Substance may be transported hot.
- For hybrid vehicles, GUIDE 147 (lithium ion batteries) or GUIDE 138 (sodium batteries) should also be consulted.
- If molten aluminum is involved, refer to GUIDE 169.

**SECTION 11. TOXICOLOGICAL INFORMATION**

| Name          | CAS Number     | LD50 Oral      | LD50 Skin         | LC50 Inhal(gas) | LC50 Inhal(mist) |
|---------------|----------------|----------------|-------------------|-----------------|------------------|
| HI HEAT       | Not applicable | 659 ATEoral    | 3135 ATEdermal    | 7519 ATEgas     | -                |
| Components :  | -----          | -----          | -----             | -----           | -----            |
| PROPAN-2-OL   | 000071-23-8    | 5840 mg (Rat)  | 16000 mg (Rabbit) |                 |                  |
| XYLENE        | 001330-20-7    | 4300 mg (Rat)  | >5000 mg (Rabbit) |                 |                  |
| N-BUTANOL     | 000071-36-3    | 750 mg (Rat)   | 3400 mg (Rabbit)  |                 |                  |
| BUTANONE      | 000078-93-3    | 3400 mg (Rat)  | 13000 mg (Rabbit) |                 |                  |
| ETHYL ALCOHOL | 000064-17-5    | 21000 mg (Rat) |                   |                 |                  |
| N-BUTANOL     | 000071-36-3    | 750 mg (Rat)   | 3400 mg (Rabbit)  |                 |                  |

**Inhalation****Skin****Eyes****Ingestion**

Irritating, narcotic. Formaldehyde may be released during curing.  
 Highly irritating. Risk of dermatitis. May be absorbed through intact skin.  
 Irritating - may cause damage if not given prompt attention.  
 Harmful if swallowed.

May cause respiratory irritation.  
 May cause cancer  
 Suspected of causing genetic defects  
 May cause an allergic skin reaction.  
 Causes serious eye damage.  
 Causes skin irritation.  
 Harmful if inhaled.  
 May be harmful in contact with skin  
 Harmful if swallowed.

**POTENTIAL HAZARDS****HEALTH**

- Inhalation or contact with material may irritate or burn skin and eyes.
- Fire may produce irritating, corrosive and/or toxic gases.
- Vapors may cause dizziness or suffocation.
- Runoff from fire control or dilution water may cause pollution.

**SECTION 12. ECOLOGICAL INFORMATION**

No available ecological data of ingredients :

May have short term environmental effects. Contain, monitor & remove  
 Aquatic toxicity : No further relevant information available  
 Persistence and degradability : No further relevant information available.

Bioaccumulative potential : No further relevant information available.  
 Mobility in soil : No further relevant information available.  
 Harmful to aquatic life with long lasting effects.  
 Harmful to aquatic life

**SECTION 13. DISPOSAL INFORMATION**

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.  
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

**Promac Paints (Pty) Ltd.**

Reg. No.: 1992/007244/07 VAT Nr: 4320226139  
 354 Derdepoort Road, Silverton, Pretoria. P.O. Box 75351, Lynnwood Ridge, 0040  
 Tel: 012 804 7305 Fax: 012 804 6188 email: info@promacpaints.co.za  
 www.promacpaints.co.za

**P.QD.029**

HI HEAT

**SECTION 14. TRANSPORT INFORMATION**

**UN Number** 1263  
**Shipping Name** PAINT OR PAINT RELATED MATERIAL, FLAMMABLE  
**IMO Class** 3 **Packing Group** I  
**Action Code** 128  
**HazChem** \*3YE

**Kemler/ HIN Code** 33**SECTION 15. REGULATORY INFORMATION****Classification reference SANS10234 (1272/2008/EC) :****Classification of the substance or mixture**

(H224) Flammable liquids, Hazard Category 1  
 (H302) Acute toxicity (oral), Hazard Category 4  
 (H313) Acute toxicity (dermal), Hazard Category 5  
 (H332) Acute toxicity (inhalation), Hazard Category 4  
 (H315) Skin corrosion/irritation, Hazard Category 2  
 (H318) Serious eye damage/eye irritation, Hazard Category 1  
 (H317) Sensitisation ^ Skin, Hazard Category 1  
 (H341) Germ cell mutagenicity, Hazard Category 2  
 (H350) Carcinogenicity, Hazard Category 1A, 1B  
 (H335) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Respiratory tract irritation  
 (H402) Hazardous to the aquatic environment ^ AcuteHazard, Category 3  
 (H412) Hazardous to the aquatic environment ^ Chronic Hazard, Category 3

**SECTION 16. OTHER INFORMATION**

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.

IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

HMIS Rating (USA) : 2 - 4 - 0 - I (Health-Flam-Reactivity-PPE)

**Abbreviations**

Code : Abbreviation : Meaning

- : : flammable

C : : corrosive

F : : highly flammable

N : : dangerous for the environment

T : : toxic

Xi : : irritant

Xn : : harmful

==== : :

: : Associated pictogram code shown in brackets

==== : :

GHS01 : : Exploding bomb

GHS02 : : Flame

GHS03 : : Flame over circle

GHS04 : : Gas cylinder

GHS05 : : Corrosion

GHS06 : : Skull and crossbones

GHS07 : : Exclamation mark

GHS08 : : Health hazard

GHS09 : : Environment

: %m/m : Percent by mass

: ATE : Acute Toxicity Estimate

: CAS : Chemical Abstracts Service

: CHIP : Chemicals (Hazard Information and Packaging for supply)

: CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

: CNS : Central Nervous System

: DIN : Standard of the German Institute for Standardisation

: DOT : Department of Transport

: EC : European Community

: EC50 : Effective Concentration (Median) for 50% of the response under test

: ECB : European Chemicals Bureau

**Promac Paints (Pty) Ltd.**

Reg. No.: 1992/007244/07 VAT Nr: 4320226139  
354 Derdepoort Road, Silverton, Pretoria. P.O. Box 75351, Lynnwood Ridge, 0040  
Tel: 012 804 7305 Fax: 012 804 6188 email: info@promacpaints.co.za  
www.promacpaints.co.za



**P.QD.029**

**HI HEAT**

- : ECHA : European Chemicals Agency, Helsinki ([http://echa.europa.eu/home\\_en.asp](http://echa.europa.eu/home_en.asp))
  - : EEC : European Economic Community
  - : EINECS : European Inventory of Existing Chemical Substances
  - : ELINCS : European List of Notified Chemical Substances
  - : GHS : Globally Harmonized System of Classification and Labelling of Chemicals
  - : HMIS : Hazardous Materials Information System (USA only)
  - : IATA : International Air Transport Association
  - : IMDG : International Maritime Dangerous Goods Code
  - : IMO : International Maritime Organization
  - : INS : Guidance on Identification and Naming of Substances under REACH, ECHA, 2007
  - : ISO : International Standards Organisation
  - : L.E.L. : Lower explosive limit
  - : LD50/LC50 : Median (50%) lethal dose/concentration
  - : mg/m3 : Milligrams per cubic meter
  
  - : MSDS : Material safety data sheet
  - : n.a. : Not available
  - : NC : No Classification
  - : No : Number
  - : OEL : Occupational exposure limit
  - : OEL-CL : Occupational exposure limit - control limit
  - : OEL-RL : Occupational exposure limit - recommended limit
  - : OHS Act : Occupational Health and Safety Act
  - : P statement : Precautionary statement
  - : PPE : Personal protective equipment
  - : ppm : Parts per million
  - : REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals
  - : RTDG : Regulations on the Transport of Dangerous Goods. Generic term that covers all modal transport regulations (ADR, RID, ADN, IMDG and ITDG)
  - : SABS : South African Bureau of Standards
  - : SANS : South African National Standards
  - : SAPMA : South African Paint Manufacturers Association
  - : SARA 313 : Toxic Release Inventory Reporting SRA Section 3
  - : SDS : Safety Data Sheet
  - : STOEL : Short-term occupational exposure limit
  - : STOT-RE : Specific Target Organ Toxicity - Repeated Exposure
  - : STOT-SE : Specific Target Organ Toxicity - Single Exposure
  - : TDG : Transport of Dangerous Goods
  - : TSCA : Toxic Substance Control Act (USA only)
  - : TWA : Time weighted average
  - : U.E.L. : Upper explosive limit
  - : UN : United Nations
  - : WHMIS : Workplace Hazardous Materials Information Systems (Canada only)
- ===== :

---

This SDS conforms with General Administrative Regulations of 6 Sept.1996 (SANS11014:2010/ISO11014:2009)  
OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)  
SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)  
All information is given in good faith but without guarantee in respect of accuracy.  
No responsibility is accepted for errors or omissions or the consequences thereof.

(Date of last issue : 25/11/2025 Date of revision : 25/11/2025)