

## TECHNICAL DATA SHEET

P.DS.187 (FB SERIES) REV01/08/2024

# PROMAC AEROSOL STRIP IT PAINT STRIPPER

**Promac Aerosol strip it paint stripper** is a vicious liquid that has a heavy-duty paint and coating remover. Rapid acting and water rinsable solvent-based paint remover for brush application. It's a non-alkali formula and it will not damage bared surfaces.

### USES

Suitable for conventional types of paints, enamels, varnishes, lacquers as well as sophisticated and polymeric coating systems on wood, plaster, steel, and most other metals. Can easily be used on vertical surfaces. Does not lift wood grain nor impair repaint ability when used correctly.

LIMITATIONS: Can not be used on plastics.

### FEATURES & BENEFITS

- Water rinsable
- Rapid stripping action
- Can be applied on vertical surfaces
- Slow-release reaction time.
- Lead less than 90 ppm
- Does not contain alkali or acid – will not damage glass, wood, metal, and plaster

### TECHNICAL INFORMATION

<b>PHYSICAL FORM</b>	An off-white viscous liquid
<b>SPREADING RATE</b>	Approximately 1m <sup>2</sup> /L per application
<b>DRYING PROPERTIES</b>	Spray on and leave for about 5 - 15min
<b>PACKAGING</b>	400mℓ
<b>THINNING</b>	Ready to use.
<b>CLEANING</b>	Clean all equipment after use with Lacquer thinner
<b>APPLICATION METHOD</b>	Spray

### DIRECTIONS FOR USE

- Ensure to work in a well-ventilated area.
- Shake can vigorously. Spray the paint stripper onto the required surface
- Always test an area on the coating or substrate before use.
- Spray a liberal coat and leave for 5 – 15 minutes or until paint has wrinkled.
- For best results use on cool or cold surfaces.
- Scrape off the lifted paint with a paint scraper. Repeat until all paint has been removed.
- Rinse off using a high-pressure water jet.
- Allow to dry before wiping off with Mineral Turpentine/Lacquer Thinners

Toll Free: 080 111 1019 | Head Office: 012 804 7305 | [www.promacpaints.co.za](http://www.promacpaints.co.za)

# TECHNICAL DATA SHEET

P.DS.187 (FB SERIES) REV01/08/2024

## DO NOT USE

- IF THE TEMPERATURE IS ABOVE 35°C
- IF IT IS RAINING OR RAIN IS FORECAST

## HEALTH & SAFETY

Flammable liquid and vapour. May cause an allergic skin reaction or serious eye irritation. If swallowed: Immediately call a poison centre or doctor / physician. Rinse mouth. Do not induce vomiting. If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice. In case of fire: Use powder or appropriate media for extinction. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fumes, gases, mist, vapours or spray. Wash hands thoroughly after handling. Use personal protective equipment as required. Contaminated work clothing should not be allowed out of the workplace. Ensure good ventilation during application and drying. Store in a well-ventilated cool area away from direct sun, heat and severe cold. Keep out of reach of children. Do not empty into drains or watercourses. Dispose of contents / container in accordance with local / regional / national / international regulations.

Keep out of reach of children animals.

## DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith, but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.